

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name and Use: HEAVYDRAW 1219 - Metal Forming Lubricant

Manufacturer: Lamson Oil Company

5060 27th Avenue, Rockford, Illinois 61109 USA

Telephone Number: (815) 226-8090

Emergency Number: Call (Infotrac) (800) 535-5053

Please call INFOTRAC in the event of a transportation or medical emergency involving a human or an animal.

2. HAZARD IDENTIFICATION



Signal Word: Warning

Physical and Health Hazards:

Skin Irritation: Category 2

Eye Irritation: Category 2

Hazard Statements:

Causes skin irritation.

Causes serious eye irritation.

Precautionary Statements:

Wear protective gloves and eye protection. Wash hands thoroughly after handling.

IF SWALLOWED: Immediately call a Poison Center or Physician. Do not induce vomiting.

IF ON SKIN (or hair) Remove immediately all contaminated clothing. Rinse skin with water.

If skin irritation occurs, get medical attention.

Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If eye irritation persists, get medical attention.

In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO₂) for extinction.

Store in a well ventilated place. Keep cool.

Dispose of contents and container in accordance with local regulations.

3. COMPONENTS

Substantial Ingredients	CAS #	Weight %	GHS Classification
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 60%	Skin Ir 2, Eye Ir 2
Proprietary performance additive package	mixture	> 10%	Skin Ir 2, Eye Ir 2
Triglycerides	8016-28-2	> 5%	None
Oleyl Ether Phosphate	39464-69-2	1%	Skin Ir 2, Eye Ir 2B

4. **FIRST AID MEASURES**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If eye irritation persists, get medical attention.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs, get medical attention.

IF SWALLOWED: Immediately call a Poison Center or Physician. Do not induce vomiting.

IF INHALED: Remove to fresh air; apply artificial respiration if necessary. Get medical attention.

5. **FIRE-FIGHTING MEASURES**

General Hazard

Petroleum materials can form combustible mixtures at temperatures at or above the flash point. Empty containers can contain residues that can cause fires or explosions when exposed to heat, flames, or sparks.

Fire-Fighting

Keep fire exposed containers cool with water spray. Separate unburning product from fire. Use carbon dioxide, foam, or dry chemical extinguishing media to put out fires.

Unusual Decomposition Products Under Fire Conditions

None

6. **ACCIDENTAL RELEASE MEASURES**

Personal Precautions

Remove greatly contaminated clothing, including shoes and wash thoroughly after contact. Launder contaminated clothing before reuse.

Environmental Precautions

Dike large spills to prevent ingress into sewers.

Eliminate all sources of ignition.

Ensure adequate ventilation.

Clean spills with absorbent and store in marked containers for disposal.

Dispose in accordance with all applicable regulations.

7. **HANDLING AND STORAGE**

Safe Handling and Storage

Do not handle, store, or dispense near open flames or ignition sources.

Keep containers inside and out of direct sunlight. Avoid extreme temperatures.

Do not reuse containers.

Incompatible Products

Avoid strong oxidizing and reducing agents.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Ventilation

Local exhaust is usually sufficient. General exhaust is preferred.

Personal Protection

Use approved respirator when airborne exposure limits are exceeded. Use petroleum oil resistant gloves to avoid prolonged contact. Wear goggles or safety glasses with splashguards.

Work Place Exposure Guide Lines

Petroleum oil mist has been assigned a TLV (ACGIH) limit of 5 mg/m³.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:	> 500 °F
Specific Gravity (water =1):	0.94
Vapor pressure (kPa):	0.002
Melting Point:	Not Applicable
Vapor Density (Air =1):	> 5
Evaporation Rate (butyl Acetate=1):	< 0.04
Solubility in water:	Insoluble
Reactivity in water:	NIL
Appearance and Odor:	Clear, amber liquid; slight odor
Flash point:	329 °F typical
Flammable Limits (volume percent in air):	LEL: Not available UEL: Not available
Autoignition Temperature:	Not available

10. STABILITY AND REACTIVITY

Stability: Unstable Stable

Conditions to Avoid: None

Incompatibility (Materials to Avoid): Strong oxidizing and reducing agents.

Hazardous Decomposition Products: Combustion may produce oxides of carbon.

Hazardous Polymerization: May Occur Will Not Occur

Conditions to Avoid: Not Applicable

11. TOXICOLOGICAL INFORMATION

This product has minimal toxicity when inhaled, ingested, or when skin or eye contact is made.

This product is not expected to cause cancer or to be a skin sensitizer.

No data is available to indicate that any ingredient is mutagenic or genotoxic.

This product is not expected to cause reproductive or developmental effects.

Contact with eyes will result in irritation.

Prolonged exposure to the skin could result in irritation or dermatitis.

Exposure to vapor or aerosol concentrations above the recommended exposure level is irritating to the eyes and respiratory tract, and may cause headaches or dizziness.

12. **ECOLOGICAL INFORMATION**

This product contains a Volatile Organic Compound: So part of it will slowly evaporate upon release. Please refer to section 6 for accidental release information.

13. **DISPOSAL CONSIDERATIONS**

This product is not suitable for disposal by either landfill or municipal sewers, natural streams or rivers. This product can be incinerated directly in appropriate equipment.

14. **TRANSPORT INFORMATION**

This product is considered non-hazardous to transport.
Transportation name: Petroleum Product - Lubricant

15. **REGULATORY INFORMATION**

All components of this product are on the U.S. EPA TSCA Inventory List.

This product does not contain a reportable chemical under SARA section 313.

16. **OTHER INFORMATION**

This document was revised 11 May 2011