

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name and Use: FORMALL 2330 - Metal Forming Lubricant

Manufacturer: Lamson Oil Company

5060 27th Avenue, Rockford, Illinois 61109 USA

Telephone Number: (815) 226-8090

Emergency Number: Call (Infotrac) (800) 535-5053

Please call INFOTRAC in the event of a transportation or medical emergency involving a human or an animal.

2. HAZARD IDENTIFICATION

No Pictogram Assigned

Signal Word: None

Physical and Health Hazards:

Not Classified

Hazard Statements:

None

Precautionary Statements:

Wear protective gloves and eye protection. Wash hands thoroughly after handling.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep cool.

Avoid release to the environment. Collect spillage.

Dispose of contents and container in accordance with local regulations.

3. COMPONENTS

Ingredients Effecting Classification	CAS #	Weight %	GHS Classification
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 50%	None
Triethanolamine	102-71-6	> 10%	None

4. FIRST AID MEASURES

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists, get medical attention.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

If skin irritation occurs, get medical attention.

IF SWALLOWED: Immediately call a Poison Center or Physician. Do not induce vomiting.

IF INHALED: Remove to fresh air; apply artificial respiration if necessary. Get medical attention.

5. FIREFIGHTING MEASURES**General Hazard**

Petroleum products can form combustible mixtures at temperatures at or above the flash point.

Firefighting

Keep fire exposed containers cool with water spray. Separate unburning product from fire. Use carbon dioxide, foam, or dry chemical extinguishing media to put out fires.

Unusual Decomposition Products Under Fire Conditions

None

6. ACCIDENTAL RELEASE MEASURES**Personal Precautions**

Remove contaminated clothing, including shoes and wash thoroughly after contact.
Launder contaminated clothing before reuse.

Environmental Precautions

Stop leak if without risk.
Dike large spills to prevent ingress into sewers or waterways.
Ensure adequate ventilation.
Clean spills with absorbent and store in marked containers for disposal.
Dispose in accordance with all applicable regulations.

7. HANDLING AND STORAGE**Safe Handling and Storage**

Do not handle, store, or dispense near open flames or ignition sources.
Keep containers inside and out of direct sunlight. Avoid extreme temperatures.
Do not reuse containers.

Incompatible Products

Avoid strong oxidizing and reducing agents.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION**Ventilation**

Local exhaust is usually sufficient. General exhaust is preferred.

Personal Protection

Use approved respirator when airborne exposure limits are exceeded. Use petroleum resistant gloves to avoid prolonged contact. Wear goggles or safety glasses with splashguards.

Workplace Exposure Guidelines

Petroleum Oil mist has a TLV limit of 5 mg/m³.
Triethanolamine has a recommended TLV of 5 mg/m³.

9. **PHYSICAL AND CHEMICAL PROPERTIES**

Boiling Point:	> 500 °F
Specific Gravity (water =1):	0.94
Vapor pressure (mm Hg):	< 1
Melting Point:	Not Applicable
Vapor Density (Air =1):	> 5
Evaporation Rate (butyl Acetate=1):	< 0.1
Solubility in water:	Emulsifies
Reactivity in water:	NIL
Appearance and Odor:	Clear, brown liquid; mild odor
Flash point:	329 °F
Flammable Limits (volume percent in air):	LEL: Not Established UEL: Not Established
Autoignition Temperature: approximately	Not Established

10. **STABILITY AND REACTIVITY**

Stability: ☐ Unstable ☒ Stable
 Conditions to avoid: None
 Incompatibility (Materials to avoid): Strong oxidizing and reducing agents.
 Hazardous Decomposition Products: Combustion may produce oxides of carbon.
 Hazardous Polymerization: ☐ May Occur ☒ Will Not Occur
 Conditions to Avoid: Not Applicable

11. **TOXICOLOGICAL INFORMATION**

This product has minimal toxicity when inhaled, ingested, or when skin or eye contact is made.
 This product is not expected to cause cancer.
 No data is available to indicate that any ingredient is mutagenic or genotoxic.
 This product is not expected to cause reproductive or developmental effects.
 Contact with eyes will result in irritation.
 Prolonged exposure to the skin could result in irritation or dermatitis.
 Exposure to vapor or aerosol concentrations above the recommended exposure level is irritating to the eyes and respiratory tract, and may cause headaches or dizziness.

12. **ECOLOGICAL INFORMATION**

This product is detrimental to the environment. .
 This product contains a Volatile Organic Compound: So part of it will slowly evaporate upon release.
 Please refer to Section 6 for accidental release information.

13. **DISPOSAL CONSIDERATIONS**

This product is not suitable for disposal by either landfill or municipal sewers, natural streams or rivers.
 This product can be incinerated directly in appropriate equipment.

14. **TRANSPORT INFORMATION**

The DOT does not regulate this product for Air or Ground shipments.
Shipping Description: Petroleum Products - Lubricant

15. **REGULATORY INFORMATION**

All components of this product are on the U.S. EPA TSCA Inventory List.

This product does not contain a reportable chemical under SARA section 313.

16. **OTHER INFORMATION**

This document was revised 01 September 2023.

INFORMATION GIVEN HEREIN IS OFFERED IN GOOD FAITH AS ACCURATE, BUT WITHOUT GUARANTEE. CONDITIONS OF USE AND SUITABILITY OF THE PRODUCT FOR PARTICULAR USES ARE BEYOND OUR CONTROL; ALL RISKS OF USE OF THE PRODUCT ARE THEREFORE ASSUMED BY THE USER AND WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. APPROPRIATE WARNINGS AND SAFE HANDLING PROCEDURES SHOULD BE PROVIDED TO HANDLERS AND USERS.